



Product Bulletin

GULFPRIDE® III H ATF

Gulfpride® III H Automatic Transmission Fluid (ATF) is a multipurpose ATF formulated with premium base stocks and advanced additive technology. It is designed for use in electronic and hydraulic controlled transmissions and can also be used in other applications such as power steering units, rotary screw compressors, & some hydraulic fluid applications.

FEATURES AND BENEFITS:

Gulfpride® III H Automatic Transmission Fluid (ATF) is a true multipurpose transmission fluid that provides the following benefits:

- Excellent wear protection
- Good anti-foam properties
- Red color for easy identification
- Outstanding oxidation resistance
- A wide range of seal compatibility
- Protection against rust and corrosion
- Superior low temperature performance providing good cold-start shifting
- Savings from one fluid for virtually all automatic transmission applications
- Superior frictional characteristics with excellent retention and smooth shifting

APPLICATIONS:

Gulfpride® III H Automatic Transmission Fluid (ATF) is recommended for pre-2006 model General Motors and post- 1981 and pre-2007 Ford automatic transmissions, as well as many imports. It is suitable for use where Allison C-4 and Caterpillar TO-2 fluids are required. Additionally, this product is suitable for use in the following applications:

- In powershift transmissions, torque converters and hydrostatic transmissions
- In some hydraulic and compressor systems where excellent low-temperature fluidity and anti-wear properties are required.

AVAILABILITY:

Gulfpride® III H Automatic Transmission Fluid (ATF) is available throughout Gulf's marketing area. Your Gulf representative or Gulf jobber can provide specific information. Need additional information? Call Gulf @ 1-800-566-GULF (4853).

Gulfpride® III H Automatic Transmission Fluid (ATF) - Typical Properties

SAE Grade		5W-20
Product Code		332022 ¹
	Test Method	
API Gravity, 60°F	ASTM D-1298	32.6
Density, lbs/gal	Calculated	7.19
Viscosity, cSt @ 40°C	ASTM D-445	37.1
Viscosity, cSt @ 100°C	ASTM D-445	7.46
Viscosity, SUS @ 100°F	ASTM D-2161	183
Viscosity, SUS @ 210°F	ASTM D-2161	52.0
Viscosity Index	ASTM D-2270	190
Brookfield Viscosity, cP @ -40°C	ASTM D-2983	17,500
Brookfield Viscosity, cP @ -20°C	ASTM D-2983	1,300
Pour Point, °F (°C) (max)	ASTM D-97	-38 (-39)
Flash Point, COC, °F (°C) (min)	ASTM D-92	370 (186)
Color	ASTM D-1500	Red

¹ Product Bulletin will be active for bulk orders that are shipped starting the week of December 31, 2006. After current packaged inventories are depleted this product bulletin will represent packaged goods that are marked with III H ATF.



AMERICAN REFINING GROUP, INC.

Master Distributor of Gulf Lubricants • 77 North Kendall Avenue • Bradford, PA 16701 • 800.566.4853 • fax 814.362.7311 • www.amref.com